



China 608rs Bearing Supplier



30207JR Bearing 2D drawings and 3D CAD models

Motorcycle Spare Parts KOYO 30207JR
Bearings Best Selling Low Noise Tapered Roller
Bearing Rodamiento 30207 Rolamento

Bearing No. 30207JR

Size	35x72x18.25 mm
Bore Diameter	35 mm
Outer Diameter	72 mm
Width	18,25 mm
d	35 mm
D	72 mm
T	18,25 mm
B	17 mm
C	15 mm
a	15,3 mm
r min.	1,5 mm
r2 min.	1,5 mm
da min.	43,5 mm
da max	44 mm
Da min	62 mm
Da max.	63,5 mm
Db min.	67 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	0,344 Kg
Basic dynamic load rating (C)	55,1 kN
Basic static load rating (C0)	60,9 kN
(Grease) Lubrication Speed	5600 r/min
(Oil) Lubrication Speed	7400 r/min



China 608rs Bearing Supplier

Calculation factor (e)	0,37
Calculation factor (Y0)	0,88
Category	Tapered Roller Bearing Assemblies
Inventory	3.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.34
EAN	0605790123009
Product Group	B04334
Precision Class	Standard
Component	Assembly
Basic Number	30207
Number of Tapered Rows	Single Row
Inch - Metric	Metric
Other Features	High Load Capacity
Long Description	Assembly; Standard Precision; 35MM Bore; 72MM Outside Diameter; 18.25MM Assembly Width; Single Row of Rollers
Category	Tapered Roller Bearings Assembly
UNSPSC	31171516
Harmonized Tariff Code	8482.20.00.00
Noun	Bearing
Keyword String	Tapered
Manufacturer URL	http://www.koyousa.com
Manufacturer Item Number	30207JR
Weight / LBS	0.758
Bore	1.378 Inch 35 Millimeter
Assembly Width	0.719 Inch 18.25 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter



China 608rs Bearing Supplier

Flange Outside Diameter	0 Inch 0 Millimeter
Bearing No.	30207JR
r(min)	1.5
r1(min)	1.5
Cr	68.8
C0r	60.9
Cu	8.95
Grease lub.	5600
Oil lub.	7400
a	15.3 mm
da(min)	43.5
db(max)	44
Da(max)	63.5
Da(min)	62
Db(min)	67
Sa(min)	3
Sb(min)	3
ra(max)	1.5
rb(max)	1.5
e	0.37
Y1	1.60
Y0	0.88
(Refer.) Mass(kg)	0.344